



VIEW

SAGEX (036) 20
SAGEX Dämmplatten
Sager AG

<http://www.sager.ch/> | info@sager.ch

Type: **Insulation | Polystyrol**

Dämmplatten

Expandierte Polystyrolplatten für universelle Anwendungen. Als Wärme- und Kälte­dämmung für Dach, Wand und Boden.

mtextur ID	20451
Manufacturer	Sager AG
Manufacturer-Email	info@sager.ch
Product Line	SAGEX Dämmplatten
Product Line Info	Expandierte Polystyrolplatten für universelle Anwendungen. Als Wärme- und Kälte­dämmung für Dach, Wand und Boden.
Material Name	SAGEX (036) 20
Type	Insulation / Polystyrol
Material Info	Dämmplatten
eBKP	C 1.2 Abdichtung, Dämmung und Bodenplatte / C 1.2 Waterproofing/insulation below ground slab / C 2.1 Aussenwandkonstruktion / C 2.1 External walls / C 4.4 Dachkonstruktion / C 4.4 Roof structure, roof slabs
IFC	IfcCovering / IfcSlab / IfcWall
Area of application (mtextur Classic)	Outside / Floor / Wall / Ceiling / Roof / Facade
Delivery zones	CH / LI
Size of the CAD & BIM texture	Height: 500.0 mm / Width: 500.0 mm

IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.

max. Length / Format	Length = 1000 mm / Width = 500 mm / Thickness = 500 mm
min. Format	Length = 700 mm / Width = 500 mm / Thickness = 10 mm
Weight	20.0 kg/m ³
Thermal Conductivity	0.036 W/mK
Fire protection class	5.1 / E
Characteristics Info	CS(10) ≥ 100 kPa (= 10000 kg/m ²) Kriechverhalten bei Druckbeanspruchung*: 20 kPa (= 2000 kg/m ²)

IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.